



This MotoCAP safety rating applies to:

Brand: Rjays

Model: Polar Control II Ladies

Type: Glove - Leather/Textile

Date purchased: 8 October 2019

Sizes tested: L and XL

Test glove gender: Female

Style: All Purpose

RRP: \$69.95

Test Results Summary:

	Rating	Score
MotoCAP Protection Rating	**	2.5
Abrasion	7/10	3.55
Seam strength	1/10	4.8
Impact	2/10	5.4
Water resistance	10/10	2.1

These gloves are fitted with impact protection for the knuckles only. There is no impact protection for the palms. There is no provision for ventilation to allow airflow movement through the glove.

Gloves - Crash Impact Risk Zones

This diagram is a pictorial representation of the crash impact risk Zones.



High risk of impact High risk of abrasion Zone 2
High risk of abrasion

Medium risk of abrasion



Abrasion Resistance

The gloves were tested for abrasion resistance in accordance with MotoCAP test protocols. The diagram below is a visual indication of the likely abrasion performance of the materials in each Zone calculated from the data in the table below. The colour coding is based on the worst performing material in each zone.



Abrasion Resistance Performance

Abrasion rating 7/10 Abrasion score 3.55

Determining Criteria	Area	Good	Acceptable	Marginal	Poor
High abrasion risk	Zone 1 & 2	> 4.0	2.7 - 4.0	1.2 - 2.6	< 1.2
Medium abrasion risk	Zone 3	2.5	1.8 - 2.5	0.8 - 1.7	< 0.8

Individual Abrasion Resistance Results: - The table below shows the test results for time to abrade through all layers of the materials. Calculated for each sample by Zone, type and area coverage of each material as a proportion of that Zone. Abrasion times are capped at a maximum of 10.00s.

Abrasion time for each test (seconds)

Zones 1	Coverage (%)	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5	Sample 6	Average	
Material A	40%	10.00	10.00	10.00	10.00	10.00	10.00	10.00	G
Material B	60%	4.57	5.17		2.15	1.85		3.43	Α
Zone 2	Coverage (%)	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5	Sample 6	Average	
Material B	60%	4.57	5.17		2.15	1.85		3.43	Α
Material C	40%			1.18	1.59	1.10	1.21	1.27	М
Zone 3	Coverage (%)	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5	Sample 6	Average	
Material B	30%	4.57	5.17		2.15	1.85		3.43	G
Material C	70%			1.18	1.59	1.10	1.21	1.27	М

Details of materials used in glove - derived from manufacturer provided information

Material A	Hard-shell armour over leather shell, water-resistant layer and loam inner liner
Material B	Leather shell, water-resistant layer and foam inner liner
Material C	Textile shell, water-resistant layer and foam inner liner



Seam Tensile Strength

The tensile strength of the gloves seams and glove restraint (the force required to drag off a properly fastened glove) were tested in accordance with MotoCAP test protocols. The diagram below illustrates the tensile strength and wrist restraint results in terms of the likely performance of the glove in a crash and is a pictorial representation of the data from the tables below.



Seam Strength Performance

Seam strength rating	1/10
Seam strength score	4.8

Determining Criteria	Unit	Good	Acceptable	Marginal	Poor
Seam tensile strength	(N/mm)	> 11	9 - 11	6 - 8.9	< 6
Glove restraint	(N)	> 200	100 - 200	50 - 99	<50

Individual Seam Strength Results: - The table below shows the seam tensile strength in newtons per millimeter (N/mm) for each seam tested by Zone and the average result for each Zone.

Seam tensile strength (N/mm)

Area	1	2	3	4	5	Average
Zones 1 & 2	5.08	5.07	4.19	4.38	4.62	4.67 P
Zone 3	4.43	7.10	5.06	4.50	3.68	4.95

Individual Glove Restraint Results: - The table below shows the force required to remove the restrained glove in newtons (N) for each of the five gloves tested and the average result.

Glove restraint (N)

Glove	1	2	3	4	5	Average
Wrist restraint	206.7	305.4	308.5	400.0	400.0	324.1 G



Impact Protection

The glove was tested for impact protection and coverage In accordance with MotoCAP test protocols. The diagram below is a visual indication of the likely performance of each impact protector calculated from the data in the table below. The colour coding is based on the worst performing score for average or maximum force for each impact zone. Areas shaded black are not considered in the impact protection ratings.



^{*} Poor may also indicate that no impact protector is present in the glove

Impact Protector Results: - The table below shows the test results for each strike on each impact protector in kilonewtons (kN) and their area of coverage in percentage (%) within the Zone. Impact forces are capped at a maximum of 10.0kN.

Impact protector type	Knuckles	Palm
Average force (kN)	2.2 A	P
Maximum force (kN)	5.0 M	Р
Coverage of zone 1 area	100%	0%

Individual test results: - The table below shows the test results for each strike on each impact protector in kilonewtons (kN) and the position of the strike. Impact forces are capped at a maximum of 10.0kN.

Impact protector type	Knuckles			Palm	No impact protector present
Strike number	1	2	3	1	2
Impact Protector 1	5.0	1.9			
Impact Protector 2	1.5	2.0			
Impact Protector 3	1.8	1.3			



Water spray and rain resistance

This glove is advertised as water-resistant, and so has been tested for water spray and rain resistance according to the MotoCAP test protocols. The table below shows the water absorbed (ml) and the wetting proportion (%) of the glove and under-glove due to water absorption.

	Water absorbe	ed by glove	Water absorbed by cotton glove		
	Volume (ml)	Percentage (%)	Volume (ml)	Percentage (%)	
Pair 1	159.0	115%	4.1	20%	
Average	159.0	115%	4.1	20%	

Location of wetting:

Visible wetting to the cotton under-glove was present over the top of the hand in one of the two gloves tested. There was minor wetting to the wrist of the other glove.

Assessment Details.

Brand Rjays

Model Polar Control II Ladies
Type Glove - Leather/Textile

Date purchased 8 October 2019
Tested by AMCAF, Deakin University

Report approved by MotoCAP Chief Scientist

Garment test reference G19L26
Rating first published March 2020
Rating updated 10 August 2021