

MOTOCAP

This MotoCAP safety rating applies to:


Brand	Rev'lt
Model	Womens Ellison SK Leggings
Туре	Pants - Textile
Date purchased	28 July 2022
Sizes tested	XXS and XS
Test garment gender	Female
Style	All Purpose
RRP	\$258.95

Test Results Summary	Rating	Score
MotoCAP Protection Rating	+	7.5
Abrasion	1/10	0.27
Burst	6/10	611
Impact	1/10	0.0
MotoCAP Breathability Rating	***	0.528
Moisture Vapour Resistance	-	20.7
Thermal Resistance	-	0.182
Water resistance	N/A	N/A

This garment is fitted with impact protectors for the knees. Pockets are provided at the hips for fitting aftermarket impact protectors. Adding hip impact protectors would improve the protection levels of this garment. There are no vents to allow airflow movement through the garment.

Jacket and Pants - Crash Impact Risk Zones

This diagram is a pictorial representation of the crash impact risk Zones.





Abrasion Resistance

These pants were tested for abrasion resistance in accordance with MotoCAP test protocols. The diagram below is a visual indication of the likely abrasion performance of the materials in each zone calculated from the data in the table below. The colour coding is based on the worst performing material in each zone.



Abrasion rating	1/10
Abrasion score	0.27

Determining Criteria	Area	Good	Acceptable	Marginal	Poor
High abrasion risk	Zones 1 & 2	> 5.6	3.0 - 5.6	1.3 - 2.9	< 1.3
Medium abrasion risk	Zone 3	> 2.5	1.8 - 2.5	0.8 - 1.7	< 0.8
Low abrasion risk	Zone 4	>1.5	1.0 - 1.5	0.4 - 0.9	< 0.4

Individual Abrasion Resistance Results: - The table below shows the test results for time to abrade through all layers of the materials. Calculated for each sample by Zone, type and area coverage of each material as a proportion of that Zone. Abrasion times are capped at a maximum of 10.00s.

Abrasion time for each test (seconds)

Zones 1 & 2	Coverage (%)	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5	Sample 6	Average
Material A	50%	0.56	0.43	0.60	0.47	0.48	0.44	0.50 P
Material B	50%	0.31	0.22	0.34	0.33	0.29	0.34	0.31 P
Zone 3	Coverage (%)	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5	Sample 6	Average
Material A	20%	0.56	0.43	0.60	0.47	0.48	0.44	0.50 P
Material B	80%	0.31	0.22	0.34	0.33	0.29	0.34	0.31 P
Zone 4	Coverage (%)	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5	Sample 6	Average
Material A	30%	0.56	0.43	0.60	0.47	0.48	0.44	0.50 M
Material B	70%	0.31	0.22	0.34	0.33	0.29	0.34	0.31 P

Details of materials used in pant

Material A	Knitted fabric shell with fabric inner liner
Material B	Knitted fabric shell



Burst Strength

These pants were tested for burst strength in accordance with MotoCAP test protocols. The diagram below illustrates the burst strength results in terms of the likely performance of the garment in an impact and is a pictorial representation of the data from the table below.



Burst Strength	Performance
Burst rating	6/10
Burst score	611

Determining Criteria	Unit	Good	Acceptable	Marginal	Poor
Burst strength	(kPa)	> 1000	800 - 1000	500 - 799	< 500

Individual Burst Strength Results: - The table below shows the burst pressure in kilopascals (kPA) for each sample tested by Zone and the average result for each zone.


Burst pressure for each seam (kPA)

Area	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5	Sample 6	Average	
Zones 1 & 2	499	491	557	675	563	770	593	Μ
Zones 3 & 4	680	667	797	519	793	645	683	Μ



Impact Protection

These pants were tested for impact protection and coverage in accordance with MotoCAP test protocols. The diagram below is a visual indication of the likely performance of each impact protector calculated from the data in the table below. The colour coding is based on the worst performing score for average or maximum force for each impact zone. Areas shaded black are not considered for impact protection ratings.



* Poor may also indicate that no impact protector, or impact protector pocket is present in the garment

Impact Protector Results: - The table below shows the average and maximum force transmitted through each impact protector type in kilonewtons (kN) and their area of coverage as a proportion (%) of the Zone.

Impact protector type	Knee		Hip
Average force (kN)	21.3	A	P
Maximum force (kN)	21.8	A	Р
Coverage of Zone 1 area	110%		0%
Coverage of Zone after displacement	90%		0%

Individual Impact Protector Results: - The table below shows the test results for each strike on individual impact protectors in kilonewtons (kN) and the position of the strike. Individual strike results are capped at a maximum of 50kN.

Force transfer for each impact strike (kN)

Impact protector type	Knee			Hip	No impact pro	tector present
Strike location	Centre	Mid	Edge	Centre	Mid	Edge
Impact Protector 1	21.3	20.9	21.8			
Impact Protector 2	21.6	20.9	20.8			
Impact Protector 3	21.7	21.2	21.6			



Breathability

These pants were tested for breathability following the MotoCAP test protocols. The table below shows the moisture vapour resistance and the thermal resistance values obtained.

Without removable liners		With water-resistant liner		
Breathability rating	***	Brea	thability rating	N/A
Breathability score	0.528	Brea	thability score	N/A
Moisture Vapour Resistance - R _{et} (kPa.m ² /W)		1	2	Average
Without removable liner	rs	20.6	20.7	20.7
With water-resistant line	er	N/A	N/A	N/A
Thermal Resistance - R _{ct} (K.m²/W)		1	2	Average
Without removable liner	rs	0.181	0.183	0.182
With water-resistant line	er	N/A	N/A	N/A

Water spray and rain resistance

This pants have not been advertised as water-resistant so has not been tested for water spray and rain resistance.

Assessment Details.

Brand	Rev'lt
Model	Womens Ellison SK Leggings
Туре	Pants - Textile
Date purchased	28 July 2022
Tested by	AMCAF, Deakin University
Report approved by	MotoCAP Chief Scientist
Garment test reference	P21T05
Rating first published	January 2023
Rating updated	31 January 2023